

INSTALLATION INSTRUCTIONS

WARNINGS: TO REDUCE THE RISK OF FIRE, ELECTRIC SHOCK, OR INJURY TO PERSONS, OBSERVE THE FOLLOWING:

1. Electrical wiring is to be carried out by a licensed electrical contractor in accordance with all applicable safety codes and standards, including fire-rated construction.
2. Before cutting a hole in the ceiling, check that there are no ceiling joists, etc. or electrical wiring above the desired mounting location.
3. The fan must be installed so that the blades are more than 2.1 meters above the floor.
4. A minimum of 500mm clear space above the fan is necessary.
5. If ducting is used it should be of a diameter larger than the fan blade.
6. Do not install the fan in canopies over stoves, etc. as excessive heat will damage the unit.
7. The supply cord of this fan cannot be replaced. If cord is damaged, discard the unit.
8. The fan is not intended for use by young children or infirm persons without supervision.
9. supervision.
10. Young children should be supervised to ensure they do not play with this fan.
11. Children should be supervised to ensure that they don't play with the appliance.
12. DO NOT attempt to modify or repair the appliance yourself - there are no user serviceable parts inside.

INSTALLATION:

CAUTION: ANY ELECTRICAL WIRING IS TO BE CARRIED OUT BY A LICENSED ELECTRICAL CONTRACTOR. DO NOT INSTALL IN AN AREA WHERE WATER MAY BE SPLASHED ON THE APPLIANCE.

IMPORTANT:

Check that no hidden timbers / wiring / pipes where the cutting hole is marked. The fan must be positioned so there is a minimum of 500mm clear space above the fan. Precautions must be taken to avoid the back-flow of gasses onto the room from the open flue of gas or other fuel-burning appliances. If a ducting is required, it must be larger than the diameter of the fan blade. Duct length if more than 1 meter will affect the fan's performance. Care must be taken in order to avoid any water ingress on the exhaust fan from the duct.

INSTALLATION STEPS -1:

Model: APB20-1A / APB25-1A

1. Ensure that a 3 pin power socket is installed the ceiling close to the mounting hole. Make sure that the supply to 3 pin power socket is Turned OFF.
2. Using the cutting template provided, insert a nail (or similar) through the centre hole and position it at the centre of the desired location.
3. Insert a pencil through the other hole. Mark the circle and cut out the hole. The diameter of the entire hole should be matched the to specific size.
4. Remove the front grille from the fan by pulling at the outer rim.
5. The exhaust fan has 3X Push Bar camps, pull the clamps outwards and place the fan into the hole.
6. Once the exhaust fan is placed inside the hole push the clamps inwards, thereby allowing fan to hold its position inside the hole.
7. Use a screwdriver to tighten the clamps screw. Do not over tighten the screws.
8. Make sure that the fan plug is accessible after the fan is installed in the respective position. Check that the electrical cord is clear of the fan blades and blades are free to rotate.
9. Replace the grille by pressing over the flange until it snaps into place. The fan is now ready for use.
10. Ensure that the fan is switched off from the supply mains before removing the guard.
11. Turn ON the power to the 3 pin power socket.

