


Rafe 33W Surface Mount Downlight IP65 BK



SKU	CS-CGD-LC1518R-01-33W-3000K-60D-IP65-BK	UGR	19
	CS-CGD-LC1518R-01-33W-4000K-60D-IP65-BK		
	CS-CGD-LC1518R-01-33W-5000K-60D-IP65-BK		
LED BRAND AND TYPE	Bridgelux COB	HOUSING COLOUR	BK
INPUT VOLTAGE (V)	220-240V; 50/60Hz	MATERIAL	ALUMINUM
PROTECTION CALSS	CLASS I	IP	65
IC-4 RATED (Y/N)	YES	IK	N/A
POWER FACTOR (PF)	0.9	OPERATING TEMPERATURE (°C)	-20°C to +40°C
WATTAGE (W)	33W	DIMMABLE (Y/N)	Yes
FLICKER FREE (Y/N)	YES	DIMMING TYPE	Traic-dimming
LUMEN OUTPUT (LM)	2970LM	INSTALLATION TYPE	SURFACE MOUNTED
EFFICACY (LM/W)	90LM/W	DIMENSION (mm)	Ø135 x H170 mm
COLOUR TEMPERATURE (K)	3000K / 4000K / 5000K	NET WEIGHT (kg)	1.6
BEAM ANGLE (°)	60°	LIFESPAN (HOURS)	50,000
CRI (Ra)	90	WARRANTY (YEARS)	3
SDCM	3	COMPLIANCE	SAA, RCM